PZL (PZ-11HP) Triplex Drilling Mud Pump



SPECIFICATIONS

 Maximum Input
 1,600 BHP (1,193 kw)

 Maximum RPM
 115 RPM

 Stroke Length
 11 in. (279 mm)

 Piston Load
 150,300 lbs. (68,175 kg)

Pump Weight 37,000 lbs. (16,815 kg)

Gear Ratio 4.38:1

| 5,000 PSI Fluid End Cylinder | | | | | | | | | | |
|------------------------------|-----|---------------------------------|--------|------------|--------|--------------|-----------|-------------|------------------|--|
| PISTON CYLINDER | | DISPLACEMENT – DRILLING SERVICE | | | | MAXIMUM PSI | | | | |
| DIAMETER | | PER REVOLUTION | | PER MINUTE | | IMAXIMUM PSI | | PUMP RPM | JACKSHAFT RPM | |
| inch | mm | gallon | liters | gallon | liters | PSI | Kg/sq.cm2 | | | |
| 7 | 178 | 5.5 | 20.82 | 632 | 2,392 | 3,905 | 275 | 115 | 504 | |
| 6.5 | 165 | 4.74 | 17.94 | 545 | 2,063 | 4,529 | 318 | | | |
| 6 | 152 | 4.04 | 15.29 | 465 | 1,760 | 5,000 | 352 | | | |
| 5.5 | 140 | 3.40 | 12.87 | 390 | 1,476 | 5,000 | 352 | | | |
| 7,500 PSI Fluid End Cylinder | | | | | | | | | | |

| | PISTON CYLINDER DIAMETER | | DISPLACEMENT – DRILLING SERVICE | | | | MAXIMUM PSI | | | |
|---|---------------------------|-----|---------------------------------|--------|------------|--------|---------------|-----------|-------------|------------------|
| | | | PER REVOLUTION | | PER MINUTE | | - MAXIMUM PSI | | PUMP RPM | JACKSHAFT RPM |
| | inch | mm | gallon | liters | gallon | liters | PSI | Kg/sq.cm2 | | |
| Ī | 7 | 178 | 5.5 | 20.82 | 632 | 2,392 | 3,905 | 275 | 115 | 504 |
| | 6.5 | 165 | 4.74 | 17.94 | 545 | 2,063 | 4,527 | 318 | | |
| | 6 | 152 | 4.04 | 15.29 | 465 | 1,760 | 5,314 | 374 | | |
| | 5.5 | 140 | 3.40 | 12.87 | 390 | 1,476 | 6,324 | 445 | | |
| | 5 | 127 | 2.80 | 10.60 | 323 | 1,223 | 7,500 | 527 | | |


Weight: Complete pump with large steel skid - 41,400 pounds.

Ratings are based on 90% mechanical efficiency and 100% volumetric efficiency.

Gardner Denver

Pumping Perfected.

PZL (PZ-11HP) Triplex Drilling Mud Pump



OPTIONAL FEATURES

- 7,500 PSI fluid
- Steel skid under pump only
- Large steel skid with non-skid decking
- Centrifugal suction charging pump
- Rubber valve inserts
- Suction and/or discharge dampeners

- Oil heat exchanger
- External electric powered lube pump
- Fabricated suction manifold
- · Custom packaging available
- Full open valves

STANDARD FEATURES

- Nodular iron power frame, eccentric, connection rods, and crossheads
- Double-row-spherical roller bearings carry eccentric
- Double extended Jackshaft carried on heavy-duty straight roller bearings
- Dual roller bearing connecting rod
- Heat-treated alloy steel, interchangeable fluid cylinders

- Three-rib API-7 urethane insert valves and seats
- Replaceable-type element oil filer and oil pressure gauge
- Threaded valve covers
- Plated piston rods
- Complete piston washing and lubrication system

SPECIFICATIONS

